

Location data enabling urban sustainable energy planning

Original

Location data enabling urban sustainable energy planning / Kona, Albana; Martirano, Giacomo; Mutani, Guglielmina. - ELETTRONICO. - (2016).

Availability:

This version is available at: 11583/2693305 since: 2017-11-23T08:51:55Z

Publisher:

Published

DOI:

Terms of use:

openAccess

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

(Article begins on next page)

The European Commission's science and knowledge service

Joint Research Centre

Location data enabling urban sustainable energy planning

Albana Kona

Giacomo Martirano (JRC external consultant)

Guglielmina Mutani (Politecnico di Torino, IT)

Barcelona, 30 September 2016
INSPIRE Conference



European
Commission





Outline

- Overview of Use Case 4 of the EULF Energy Pilot
- Role of INSPIRE
- Energy Efficiency driven retrofit planning
- Mapping energy consumption
- Urban context variables
- Feasibility index
- Energy saving scenarios
- Input data

Overview of the EULF Energy Pilot UC4




- Goal: To support policy makers to design and implement Energy Efficiency driven renovation plans of building stock at urban level.
- Description: Use of existing models, from bottom-up to top-down approach, for the estimation of energy needs at urban level, based on real energy consumption data of a sample of buildings:
 - for building stock renovation planning and prioritization of interventions, e.g. by class of buildings and/or geographical area of interventions (e.g. in areas having energy distribution networks or in historical centres);
 - to enable Public Authorities (e.g. Municipalities) to assess the energy saving potential related to the building stock and to local conditions (e.g. climate);
 - to allow reuse of scaling-up models (from building to urban level) in different climatic conditions and with different characteristics of the building stock.






Role of INSPIRE

- Introduce INSPIRE into a methodology already applied to a test area (without INSPIRE), in order to facilitate the re-use of the methodology in other geographical contexts

Energy Efficiency driven retrofit planning



Mapping energy consumption




Renewable energy sources potential (Cities On Power)

Urban context variables


$$\text{kWh/m}^3_{[\text{CONTEXT}]} = f(\mathbf{BD}, \mathbf{BCR}, H/W, H/H_{\text{avg}}, \text{MOS}, A)$$

BD – Building Density [m^3/m^2]


BCR – Building Coverage Ratio [m^2/m^2]



$$\text{BD} = \text{BCR} \cdot \text{Building Height}$$



$$\text{BCR} = \frac{\text{Built Area}}{\text{Site Area}}$$




16

Mapping energy consumption




Case study: Turin (IT)



$$\left. \frac{kWh}{m^3} \right|_{\text{measured}} = \left. \frac{kWh}{m^3} \right|_{\text{building}} \pm \left. \frac{kWh}{m^3} \right|_{\text{context}}$$




Mapping energy consumption



$$T_{air} = 23.05 \cdot G_{mT} + 2.69 \cdot BCR + 0.03 \cdot H/W + 0.65 \cdot MOS + 1.07 \cdot H/H_{avg} - 1.17 \cdot A - 0.6 \cdot H_2O$$



Feasibility index



Age factor:

active population (24-65) / total population

Variables: ECONOMIC, DECISION, INTEREST

Education factor:

population with scholastic graduation / total population

Variables: AWARENESS

Employment factor:

employed people / total population

Variables: ECONOMIC, CREDIT ACCESS

Building's occupation factor:

percentage of occupied buildings

Variables: DECISION, INTEREST


Period of construction factor:

buildings built before 1945



Variables: DECISION, INTEREST PROCESS

	First class	Second class	Third class	Fourth class
Feasibility index	<0.42	0.42 - 0.50	0.50 - 0.58	> 0.58
Number of buildings in the Metropolitan City of Torino	13%	42%	39%	6%
Number of buildings in Torino	20%	54%	23%	3%
Renovation level	windows substitution	+ boiler substitution	+ thermal insulation of slab and roof	+ thermal insulation of facades

Feasibility index



Energy savings scenarios



Input data

- | | |
|---|--------|
| • energy consumption data at building level | BU ext |
| • building characteristics | |
| • energy networks | US |
| • land use | LU, LC |
| • population distribution | SU+PD |
| • socio-economic variables | |

Stay in touch



JRC Science Hub: www.ec.europa.eu/jrc



YouTube: JRC Audiovisuals



Twitter: @EU_ScienceHub
@EULocation



Vimeo: Science@EC



LinkedIn: european-commission-joint-research-centre



<http://inspire.ec.europa.eu/>



website: http://ec.europa.eu/isa/actions/02-interoperability-architecture/2-13action_en.htm

EULF Joinup Community: <https://joinup.ec.europa.eu/community/eulf/description>

Email: eulf-info@jrc.ec.europa.eu